

# KT90DGME

<b>Product family</b>	Hood
<b>Hood Type</b>	Decorative wall hood
<b>Design</b>	Chimney
<b>Extraction</b>	Extraction
<b>Material</b>	Painted material
<b>Type of steel</b>	Brushed
<b>EAN code</b>	8017709334062
<b>Hood width</b>	90 cm



## Aesthetics

<b>Aesthetic Serie</b>	Victoria	<b>Finishing Collaborations</b>	Glossy
<b>Colour</b>	Divina Cucina	<b>Logo</b>	Smeg & Dolce&Gabbana
<b>Decoration / Special colour</b>	Decorated / Special		Applied
	Blu Mediterraneo		

## Controls

<b>Control setting</b>	Control knobs	<b>Control knobs</b>	Victoria
<b>No. of controls</b>	2	<b>Controls colour</b>	Steel effect

## Programme / Functions

<b>No. of speeds</b>	3
<b>Intensive speed</b>	

## Technical Features

			
<b>No. of lights</b>	2	<b>No. of filters</b>	3
<b>Light type</b>	LED	<b>Anti-grease filters</b>	Stainless steel
<b>Light Power</b>	1 W	<b>Vent outlet</b>	150 mm
<b>Light color temperature scale (°K)</b>	3000 °K	<b>Minimum distance from GAS hob</b>	750 mm

Free outlet maximum capacity	820 m <sup>3</sup> /h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	334	49
Speed 2	439	57
Speed 3	567	61
Intensive speed	788	69

## Performance / Energy Label

<b>A</b>	Annual Efficiency Consumption (AEChood)	59 kWh/a	Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)	49 dB(A)
	Energy efficiency class (EEC)	A	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	61 dB(A)
	Fluid Dynamic Efficiency (FDE)	30	Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)	69 dB(A)
	Fluid Dynamic Efficiency class (FDEC)	A	Time increase factor (F)	1.00
	Lighting Efficiency (LE)	102.3 lux/W	Energy Efficiency Index	52.4
	Lighting Efficiency Class (LEC)	A	Measured air flow rate at best efficiency point (Qbep)	438 m <sup>3</sup> /h
	Grease Filtering Efficiency (GFE)	76.6 %	Measured air pressure at best efficiency point (Pbep)	434 Pa
	Grease Filtering Efficiency Class (GFEC)	C	Measured electric power input at best efficiency point (Wbep)	176 W
	Air flow at minumum speed (Qmin)	334 m <sup>3</sup> /h	Nominal Power consumption of the light system (WL)	2 W
	Air flow at maximum speed (Qmax)	567 m <sup>3</sup> /h	Average illumination of the light on the cooking surface (Emiddle)	225 lux
	Air flow at boost speed (Qboost)	788 m <sup>3</sup> /h	Sound power level at highest setting (Lwa)	61 dB(A)

## Electrical Connection

Frequency (Hz)	50-60 Hz
----------------	----------

---

<b>Electrical connection rating</b>	278 W	<b>Power supply cable length</b>	1000 mm
<b>Voltage</b>	220-240 V		

## Also available

---

<b>Alternative colours available</b>	Sicilian Cart	<b>Available colours</b>	KT90DGC
--------------------------------------	---------------	--------------------------	---------

## Not included accessories

---



### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary (TT)

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



**A:** Product drying performance, measured from A+++ to D / G depending on the product family



**Intensive/turbo setting:** when extra fast extraction is required.